

# LED CEILING



## Feature

- High transmission white acrylic lens
- Available in wide range of color temperature
- Ambient temperature:  $-20^{\circ}\text{C}$  to  $40^{\circ}\text{C}$
- 3 years limited warranty
- 10"/12"/14"/16"/18" bulge ceiling lights
- No Flicker, no glare

## Applications

- Widely used to replace incandescent light bulb at indoor fixtures, pendant lamp fitting and other applications.

## Technical Specifications

| Part No.    | Wattage (W) | Voltage  | Luminous (lm) | PF  | CRI (Ra) | Dimension (mm) | CCT (K)   | beam angle |
|-------------|-------------|----------|---------------|-----|----------|----------------|-----------|------------|
| LED C10 14W | 14          | 100-250V | 980           | 0.9 | 80       | 256*76         | 2700-6500 | 116°       |
| LED C12 18W | 18          | 100-250V | 1260          | 0.9 | 80       | 308*84         | 2700-6500 | 116°       |
| LED C14 22W | 22          | 100-250V | 1540          | 0.9 | 80       | 360*88         | 2700-6500 | 116°       |
| LED C16 26W | 26          | 100-250V | 1820          | 0.9 | 80       | 410*108        | 2700-6500 | 116°       |
| LED C18 30W | 30          | 100-250V | 2100          | 0.9 | 80       | 457*113        | 2700-6500 | 116°       |

