

# LED RIMLESS PANEL



## Feature

- Ultra Slim, Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot be easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or Mercury content
- Environment friendly
- Dimmable options available in selected models

## Applications

- Office Lighting
- Conference Halls
- Hospitals
- Hotels
- Shopping Malls
- Showroom and lobby cabin etc
- Kitchen and Domestic Lighting

## Technical Specifications

Part No.	Wattage (W)	Luminous (lm)	CRI (Ra)	Voltage (V)	CCT (K)	Dimension (mm)
STD STRPL 8W	8	560	80	220-240V	3000K/4000K/6400K	95*95
STD STRPL 15W	15	1500	80	220-240V	3000K/4000K/6400K	145*145
STD STRPL 22W	22	2200	80	220-240V	3000K/4000K/6400K	170*170
STD STRPL 29W	29	2800	80	220-240V	3000K/4000K/6400K	200*200
STD RTRPL 8W	8	560	80	220-240V	3000K/4000K/6400K	270*100
STD RTRPL 15W	15	1500	80	220-240V	3000K/4000K/6400K	270*145
STD RTRPL 22W	22	2200	80	220-240V	3000K/4000K/6400K	270*170
STD RTRPL 29W	29	2800	80	220-240V	3000K/4000K/6400K	270*200

