



LED flood light



Features




- Slim LED Flood Light saving 50% cost compare with classic flood light
- 180°Adjustable Bracket
- Build-in power supply, no external ballast required
- Durable housing, die cast aluminum, scratch and fade resistant.
- Eco Friendly. No lead or mercury. No Hazardous Emissions. No UV or IR Radiation.

Applications

- idea for lighting, Gardens, Bill Boards, Sports Grounds, and Parking Lots etc.

Technical Specifications

Part No.	Wattage (W)	Voltage	Luminous (lm)	PF	CRI (Ra)	CCT (K)	Beam angle	IP	Working Temperature(°C)
DS-PROFD10	10	220-240V	800	0.9	>80	3000K/4000K/6500K	120°	IP65	-25° ~ 45°
DS-PROFD20	20	220-240V	1600	0.9	>80	3000K/4000K/6500K	120°	IP65	-25° ~ 45°
DS-PROFD30	30	220-240V	2400	0.9	>80	3000K/4000K/6500K	120°	IP65	-25° ~ 45°
DS-PROFD50	50	220-240V	4000	0.9	>80	3000K/4000K/6500K	120°	IP65	-25° ~ 45°
DS-PROFD100	100	220-240V	8000	0.9	>80	3000K/4000K/6500K	120°	IP65	-25° ~ 45°



✖ It can be available for wide voltage

www.edisunlighting.com

