

LED Light AR111



Features




- Unique heat sinking design.
- Green environment, impact resistance, shock proof, no lead, no mercury, no UV, no IR.
- Input and output constant current drivers work separately, making sure high power LEDs work safety.
- The power supply prevents from high temperature and short circuit.
- Long Lifespan: 25, 000 hours
- 80%~90% energy saving
- Available base: G53 , GU10

Applications

- Landscape Accent / Spot lighting, Architectural Lighting, Display Case Accent, Artwork Lighting, Mood Lighting / General lighting Amusement Park Accent, Decorative lighting

Technical Specifications

Part No.	Wattage (W)	Voltage (V)	Luminous (lm)	PF	CRI (Ra)	CCT	Beam angle	Light size (mm)
DS-AR111-SMD-12W	12	180-265V	960	0.5	>80	2700/4000/6400	36°	68*111
DS-AR111-SMD-15W	15	180-265V	1200	0.5	>80	2700/4000/6400	36°	68*111
DS-AR111-SMD-12W-Dim	12	180-265V	960	0.5	>80	2700/4000/6400	36°	68*111
DS-AR111-SMD-15W-Dim	15	180-265V	1200	0.5	>80	2700/4000/6400	36°	68*111



* It can be available for wide voltage

www.edisunlighting.com

