

LED Panel



Features




- Ultra Slim Design
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or mercury content, environmental protection
- Dimmable options are available in selected models

Applications

- Office Lighting(Conference Room,Hospitals,Hotels,Shopping Malls, Showroom and lobby cabin etc.)Kitchen and Domestic Lighting

Technical Specifications

Part No.	Wattage (W)	Voltage	Luminous (lm)	PF	CRI (Ra)	CCT (K)	Light size (mm)	Working Temperature(°C)
STD PL6060 36	36	85-265V	3600	>0.5/>0.9	80	3000-5000K	595*595*10	-20°~40°
STD PL6060 48	48	85-265V	4800	>0.5/>0.9	80	3000-5000K	595*595*10	-20°~40°
STD PL3060 24	24	85-265V	2100	>0.5/>0.9	80	3000-5000K	595*595*10	-20°~40°
STD PL30120 36	36	85-265V	3600	>0.5/>0.9	80	3000-5000K	295*1195*10	-20°~40°
STD PL60120 72	72	85-265V	7000	>0.5/>0.9	80	3000-5000K	595*1195*10	-20°~40°



✦ It can be available for wide voltage

www.edisunlighting.com

