

LED ceiling light



Features



- Outdoor Advertising LED backlight instead of the fluorescent light box
- Super slim, Saving freight
- Integrated LED design IP65
- Convenient Installation
- Direct replacement of the same size as the ceiling lighting
- Build in Driver

Applications

- Balcony, corridor, courtyard, parking lot, bathroom, kitchens, stairwells, Indoor signs backlight, such as cabinet light, shopping malls, hotel restaurant advertising signs architectural lighting

Technical Specifications

Part No.	Wattage (W)	Voltage	Luminous (lm)	PF	CRI (Ra)	Dimensions (mm)	CCT (K)	Beam angle	IP	Working Temperature(°C)
DS-CL-R8	8	220-240V	640	0.5	>80	170*48	2700-6000K	120°	IP65	-20° ~ 40°
DS-CL-R12	12	220-240V	900	0.5	>80	170*48	2700-6000K	120°	IP65	-20° ~ 40°
DS-CL-R15	15	220-240V	1200	0.5	>80	210*48	2700-6000K	120°	IP65	-20° ~ 40°
DS-CL-R18	18	220-240V	1400	0.5	>80	210*48	2700-6000K	120°	IP65	-20° ~ 40°
DS-CL-R20	20	220-240V	1600	0.5	>80	238*49	2700-6000K	120°	IP65	-20° ~ 40°
DS-CL-R24	24	220-240V	1900	0.5	>80	238*49	2700-6000K	120°	IP65	-20° ~ 40°



✳ It can be available for wide voltage

www.edisunlighting.com

